

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20310)

Point for the center ¼ sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T 25 S R 7 W

C ¼ S 5
1997

from which

A fir, 21" diam., bears N.70°E., 4½ lks., mkd. C ¼ S5 BT.

A fir, 22" diam., bears S.18°E., 33½ lks., mkd. X BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Mark Smalley - For: Roseburg Resources - 1/2002 - C.S. File 65/42-2

Found - 1997 BLM brass cap on iron pipe.
23" Fir bears N.70°E., 3.0' Good condition, healed face.

23" Fir bears S.18°E., 22.1' good condition, scribe visible.

New - 20" W.Fir N.47°W., 31.6', "C ¼ S BT"

10" D.Fir N.88°E., 29.8', "C ¼ S BT"

Fd. Ok by Troy Rambo, Aug. 2004 - M145-33