

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32 of T24-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 8 Page 3193)

Set ¼ sec. post, from which
 A Cedar 12" dia., bears S.80°W., 80 lks. dist.
 A Fir 40" dia., bears N.80°W., 35 lks. dist.

Larry D. Bishop, For: B.N. Glanville, March 9, 1970
C.S. File 55/140; M 33-68

Set Brass cap mkd: T 24 S R 7 W
 S 32
 ¼ S 5 1970 896
 T 25 S R 7 W

Bearing trees:
 11" Hemlock S.73°E., 14.3 ft. scribed ¼ S5 T25S R7W BT.
 12" Cedar N.31°E., 31.5 ft. scribed ¼ S32 T24S R7W BT.
See letter concerning this corner in C.S. File.

Fd. Ok by R. Pinard, 6/1978 - M 70-22

BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20296-7)

The ¼ sec. cor. of secs. 5 & 32, reestablished by Bishop, in 1970, and perpetuated by Pinard, in 1978. There is no remaining evidence of the original corner, therefore this position is accepted as the corner; monumented with an iron post, 1½" diam., firmly set, projecting 6" above ground, with brass cap mkd. T 24 S R 7 W

 1970 32
 5 896

 T 25 S R 7 W

from which the remains of bearing trees mkd. by Bishop
 A cedar, 20" diam., bears N.29 ¾°E., 47½ lks. with
 healed blaze.
 A hemlock snag, 20" diam., bears S.76½°E., 20½ lks., with
 healed blaze.
and a new bearing tree
 A fir, 12" diam. bears S.35 ¾°W., 43½ lks. mkd. ¼ S5 BT