

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5 of T.26-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 9 Page 3857)

Set post corner secs. 4, 5, 32 and 33, from which
A Fir 30" dia., bears N.80°E., 28 lks.
A Fir 30" dia., bears S.70°E., 71 lks.
A Fir 30" dia., bears N.50°W., 60 lks.
A Fir 12" dia., bears S.85°W., 140 lks.

GLO survey by S.C. and A.R. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 9 Page 3900)

Set new post to corner, from which
(All the old witness trees found.)

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June 14, 1966 - C.S. File 54/10-5

Found - Orig. 30" now 50" Fir N.80°E., 18.5 ft., shows old bark scribe "S R7W" & fragmentary scribe. Alive.

Orig. 30" now 43" Fir N.50°W., 39.6 ft., shows "S" bark scribed & fragmentary letters. Alive.
Other BTs down.

Set Brass cap at cor. mkd: County Surveyors T25S R7W S 32 | S 33
Office, 1966 T26S R7W S 5 | S 4

New BTs - 10" Maple N.50°W., 10.0 ft. mkd. T25S R7W S32 CSBT.
8" D.Fir S.63°W., 18.2 ft. mkd. T26S R7W S5 CS BT.
19" D.Fir S.22°E., 24.6 ft. mkd. T26S R7W S4 CS BT.

Corner lies 4.0 ft. east of small, dry creek, course S. curving to SE.

David Edwards - For: Seneca Jones Timber Co. - March 9, 2011 - C.S. File 65/74-3

Found - Brass cap
63" Fir N.80°E., 18.5'
All other BTs gone.

New BTs- 8" Fir N.5°E., 22.0'
6" Fir N.37°W., 27.4' Both scribed per BLM manual
6' steel post set 1.5' north.