

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W. H. Byars under Contract #202 dated Mar. 11, 1874 (DCSO records, Volume 9 Page 3892)

-----  
Set Fir post, for corner, from which  
A Cedar 30" dia., bears N.12°E., 12 lks. dist.  
A Laurel 14" dia., bears S.39°E., 11 lks. dist.  
A Laurel 4" dia., bears S.63½°W., 11 lks. dist.  
A Cedar 30" dia., bears N.18°W., 45 lks. dist.

-----  
GLO survey by Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Vol. 9 Page 3905)

-----  
I go to the established NE cor. of sec. 32, which is a badly decayed Oak post, in its place, a new Laurel post, 3 ft. long, 4" sq. 24" in the ground mkd. T25S S28 on NE.; N7W S33 on SE., S32 on SW.; and S29 on NW faces, with one notch on S & 4 notches on E edges.

The old witness trees having all been destroyed by fire, I therefore establish new BTs as follows:

- A Cedar 12" dia., bears N.10°E., 322 lks. dist., marked T25S R7W S28 BT. (This being out of limits, I dig pit 18 x 18 x 12 ins. NE of cor. 5½ ft. dist.
- No living tree within limits in Sec. 33, dig pit 18x18x12 ins. 5½ ft. dist. SE of cor. and raise mound of earth 4 ft. wide, 2 ft. high. W. of corner.
- A Fir 30" dia., bears S.29°W., 170 lks. dist., marked T25S R7W S32 BT.
- A Fir 30" dia., bears N.86°W., 152 lks. dist., marked T25S R7W S29 BT.

-----  
BLM resurvey by Lynn Roseberry, under Group #645. Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Page 14969)

-----  
The sec. cor., determined at record distance from the original bearing trees

- A Cedar 37" dia., bears N.11°E., 322 lks. dist. with scribe marks T25S R7W S28 BT visible on open blaze. (Record, N.10°E.)
- A Fir 43" dia., bears S.29½°W., 170 lks. dist. with a healed blaze. (Record, S.29°W.)
- A Fir 51" dia., bears S.83°W., 152 lks. dist., with a healed blaze. (Record N.86°W.)

At the corner point, Set a Iron post, 18 ins. long, and in a mound of stone, 2 ft. base, to top, with brass cap marked:  
(Cont. Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 25 S R 7 W  
S 29 | S 28  
S 32 | S 33  
1968

from which

A Fir 15" dia., bears S.83½°E., 27 lks. dist. mkd.  
T25S R7W S33 BT.

A Fir 22" dia., bears N.49°W., 41½ lks. dist., mkd.  
T25S R7W S29 BT.

BLM survey by Popken, 1975, found brass cap & five BTs.  
(DCSO records, Volume 37 Page 15306)

Fd. Ok by D. Edwards, 8/1999 - C.S. File 65/25-6