

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 Page 3892)

Set Laurel Post for $\frac{1}{4}$ sec. cor., from which
A Fir 10" dia., bears N.1 $\frac{1}{2}$ °E., 79 lks. dist.
A Cedar 60" dia., bears N.55°W., 72 lks. dist.

Bureau of Land Management resurvey by Lynn Roseberry, under Group #645 - Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Pages 14969-70)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd: T 25 S R 7 W

$\frac{1}{4}$
S 29|S 28
1968

from which
A Fir 6" dia., bears N.68 $\frac{1}{2}$ °E., 23 lks. dist., mkd.
 $\frac{1}{4}$ S28 BT.
A Fir 7" dia., bears N.86°W., 31 $\frac{1}{2}$ lks. dist., mkd.
 $\frac{1}{4}$ S29 BT.

Corner falls on a spur, slopes N.70°W.

Found OK by D. Edwards, Feb. 2004 - M144-13
Fd. Ok by D. Edwards, Feb. 2006 - M149-71