

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

Original - W. H. Byars, under Contract #202, dated March 11, 1874 (DCSO records, Volume 9 Page 3891)

Set Fir post, for cor. to secs. 20, 21, 28 and 29, from which

- A Fir 48" dia., bears N.47°E., 39 lks. dist.
- A Fir 8" dia., bears S.28½°E., 41 lks. dist.
- A Fir 60" dia., bears S.70°W., 25 lks. dist.
- A Fir 10" dia., bears N.55°W., 46 lks. dist.

BLM resurvey by Lynn Roseberry, under Group #645, Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Pgs. 14970-71)

The sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A Fir stump 50" dia., bears N.47°E., 38 lks. with no marks visible.
- A Fir stump 60" dia., bears S.70°W., 25 lks. with no marks visible.

At the corner point
Set a Iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, to solid rock, with brass cap mkd: T 25 S R 7 W

| | | | |
|--|-------------|--|-------------|
| | <u>S 20</u> | | <u>S 21</u> |
| | S 29 | | S 28 |
| | 1968 | | |

from which new bearing trees:

- A Fir 37" dia., bears N.66½°E., 90 lks., mkd. T25S R7W S21 BT.
- A Fir 13" dia., bears S.82¾°E., 56½ lks., mkd. T25S R7W S28 BT.
- A Fir 45" dia. bears S.4°W. 71½ lks. mkd. T25S R7W S29 BT
- A Fir 8" dia. bears N.49½°W., 35 lks mkd. T25S R7W S20 BT

Fd. BC by D. Edwards, 5/2007 - M153-11