

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3882)

-----  
Set Post corner, secs. 16, 17, 20 and 21, from which  
    An Oak 6" dia., bears S.80°E., 21 lks.  
    A Fir 24" dia., bears N.45°E., 80 lks.  
    A Fir 36" dia., bears N.45°W., 28 lks.  
    A Laurel 12" dia., bears S.80°W., 28 lks.

Claude Kerr, November 1953, C.S. File 41/228

-----  
Found - 26" Fir with scribing instead of the 12" Laurel as called for in field notes. Faces properly for the original BT.

Set a 6" x 8" x 12" stone for corner from the BT. Stone marked with 2 notches on South side and 4 notches on north side, from which

    Orig. 26" Fir bears S.80°W., 18.5 ft.  
New BTs - 5" Fir bears N.18°W., 11.4 ft. marked S17 BT.  
          16" Maple bears South 10.5 ft. marked S21 BT.  
          6" Fir bears N.11°E., 22.5 ft. marked S16 BT.

Fd OK, DCSO by Vernon Tracy - March 1967 C.S.54/10-9A

BLM resurvey by Lynn Roseberry, under Group #645, Survey, July 1967/Sept. 1968 (DCSO records, Vol. 36 Pg. 14974)

-----  
The sec. cor., perpetuated and recorded by Claude Kerr, Registered Engineer #2125, in 1953, monumented with a stone 12 x 8 x 6 ins., firmly set 6" in the ground, mkd. with 4 notches on N. and 2 notches on S. side, and a cross on the top, and an iron rod, protruding 6" above ground, firmly set, from which the remaining original bearing tree:

    A Fir 26" dia., bears S.84½°W., 27 lks. dist.,  
        with scribe marks S20 visible on opened blaze.  
        (Rec. Laurel, S.80°W., 28 lks.)  
and bearing trees mkd. by Kerr in 1953  
    A Fir 8" dia., bears N.13½°E., 35 lks. dist.,  
        with a healed double blaze.  
    A Maple 16" dia., bears S.1°W., 16 lks. dist.,  
        with a healed double blaze.  
    A Fir 7" dia., bears N.16°W., 18 lks. dist.,  
        with a healed double blaze.

(Cont. Next page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point  
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground directly over the iron rod, with brass cap mkd:

T 25 S R 7 W

S 17 | S 16

S 20 | S 21

1968

Deposit the stone alongside the iron post.

Found OK, Tom Shrum, December 13, 1982 - M 93-43

Found OK, Carl Sweeden, Sept. 28, 1997 - M 127-69