

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8 and 9 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Pages 3908-09)

Set a yew post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 8, 9, 16 and 17, marked T25S S9 on NE.; R7W S16 on SE.; S17 on SW.; and S8 on NW faces with 4 notches on S and E edges, from which

A Fir 36" dia., bears N.49°E., 29 lks. dist., mkd.
T25S R7W S9 BT.

A Maple 12" dia., bears S.35°E., 46 lks. dist., mkd.
T25S R7W S16 BT.

A Maple 6" dia., bears S.47°W., 32 lks. dist., mkd.
T25S R7W S17 BT.

A Fir 10" dia., bears N.37°W., 8 lks. dist., mkd.
T25S R7W S8 BT.

(Note: on Page 3914, Volume 9, Heydon erased marks on post and bearing trees on "objective" corner referring to 16 and 17)

Doug. County Surveyors Office - Vernon Tracy; V. Perron and Don Collins, BLM. May 4, 1970 - C.S. File 54/10-17 (see also C.S. 49/76-4 for 1958 or 1959? Report)

Found - Sandstone 7"x10"x14" mkd. "+" on top, not recorded in field notes.

Orig. 36" now 48" Fir snag, N.49°E., 19.1 ft., bark scribed "T25S R7W S9".

No other original BTs found.

Set Brass cap at cor. mkd: County Surveyor's T 25 S R 7 W
Office S 8 | S 9
1970 S 16

Reset old stone alongside.

New BTs - 8" W.Fir S.25°W., 4.1 ft. mkd "T25S R7W S16 CS BT".

9" Chinquapin N.32°W., 25.9 ft. mkd. "T25S R7W S8 CS BT".

No suitable tree close in section 9.

This corner lies on moderate easterly slope.

C.C. secs. 16 and 17 bears West, 147 ft.

BLM resurvey by Rick McMullen, under Group #1246 - Survey, Aug/Sept. 1985 (DCSO records, Volume 47 Page 18171)

The cor. of secs. 8 and 9 only, perpetuated and recorded by Vernon Tracy, Deputy, in 1970, monumented with an iron pipe 1" dia., firmly set, projecting 12" above ground (alongside of which is a sandstone, 10 x 7 x 4 ins. mkd. X on top) with 1970 county brass cap.

(Cont Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. cor. for 8 and 9 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree:
A Fir snag, 48" dia., bears N.49°E., 31 lks. dist.,
with scribe marks T25S R7W S visible on bark
blaze. (Record, 29 lks.)
and bearing trees mkd. by Tracy:
A Fir 12" dia., bears N.25°W., 6 lks. dist., with healed
blaze.
A Chinquapin 12" dia., bears N.32°W., 39 lks. dist.,
with illegible scribe marks visible on partially
healed blaze.
and a new bearing tree:
A Fir 8" dia., bears N.87¼°E., 59 lks. dist., mkd. T25S
R7W S9 BT.
Corner is located on NE slope, in heavy timber and dense
undergrowth.