

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3880)

-----  
Set ¼ sec. post, from which  
    An Oak 10" dia., bears S.2°W., 515 lks.  
    An Oak 20" dia., bears S.10°E., 290 lks.

Geo. E. Streese; Ed Mosher; Hermon Itreese; K. Emmett  
Dec. 18, 19, 1923 - Vol. 3 Page 175; C.S. File 2/25B;  
Field Book 52; "old" corner book, Page 57

-----  
Renewed corner from original bearing trees which are standing and bearing scars, but nearly dead.  
I set a 1½" x 24" pipe and a 4 x 4 x 30 inch Cedar post, from which old BTs  
    30" Oak S.10°E., 191.4 ft.  
    15" oak, scarred, bears S.1°30'W., 334 ft.  
New BTs - W.Oak 12" N.47°00'E., 119.5 ft.  
          W.Oak 16" S.64°15'W., 81.8 ft.

Doug. County Surveyors Office - Milo Godfrey, Deputy; Vernon Tracy; Clete Putnam - Dec. 1961 - C.S. File 49/76-16

-----  
Found - 1½" I.P. set by Streese.  
    W.Oak now 20" N.47°E., 110.1 ft. (instead of 119.5 ft.) has been previously opened, scribing visible "¼S BT". This tree is now hollow, condition poor. Probably scribing will not be visible many more years.  
    W.Oak now 26", S.64¼°W., 81.8 ft. Axe scars faintly visible. Tree is in good condition. Did not open.  
New BTs - 12" D.Fir S.36°E., 13.5 ft. mkd: "¼ S9 CS BT".  
          12" D.Fir N.82°W., 19.7 ft. mkd: "¼ S8 CS BT".

Fd. Pipe and SE BT. March 1985, Robert Dolan, M 98-42

BLM resurvey by Rick McMullen, under Group #1246 - Survey, Aug./Sept. 1985 (DCSO records, Volume 47 Pages 18171-72)

-----  
(Cont. Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

The ¼ sec. cor., perpetuated by the County in 1923, further perpetuated by Godfrey in 1961, monumented with an I.P. 1½" dia., firmly set, projecting 4" above ground, from which an original bearing tree:

An Oak 37" dia., bears S.10°E., 290 lks. dist., no marks visible on open burned blaze.

and bearing trees mkd. by the County in 1923:

An Oak 20" dia., bears N.46½°E., 167 lks. dist., no marks visible on open blaze.

An Oak 29" dia., bears S.64¼°W., 124 lks. dist., with healed blaze.

and bearing trees mkd. by Godfrey:

A Fir 28" dia., bears S.36°E., 20½ lks. dist., with healed blaze.

A Fir 25" dia., bears N.82°W., 30 lks. dist., with healed blaze.

At the corner point

Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 25 S R 7 W

¼  
S 8 | S 9  
1985

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Brass cap, Dec. 1992, M. Heimbürger, M 112-64

Fd. Brass cap, Sept. 1993, M. Heimbürger, M 117-59