

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3880)

Set post cor., secs. 4, 5, 8 and 9, from which
An Oak 18" dia., bears S.3°E., 420 lks.
An Oak 20" dia., bears S.5°W., 360 lks.
An Oak 20" dia., bears N.70°E., 275 lks.
An Oak 18" dia., bears N.87°W., 1525 lks.

J.W. Cole, Surveyor - Wit: Herman Itreese; K. Emmett
December 1923 - Field Book 52 Pg. 11 & "Old" corner book,
Page 57

Renewed corner from 4 original BTs. I set a ¾ x 30" Iron pin from which
Oak bearing scars, N.70°E., 193 ft. horizontal measure.
Oak bearing scribe, S.1°30'E., 277 ft. slope measure.
Oak bearing scribe, S.5°W., 237.2 ft. slope measure.
Oak bearing scribe, down, N.87°W., 1011.7 ft.
A boulder marked with X, S.36°E., 50 ft.
Corner in middle of spur leading up main ridge.

BLM resurvey by Irving Zirpel, under Group #411 dated August 1958 - Survey, 1958 (DCSO records, Volume 29 Page 12404)

The sec. cor., perpetuated and recorded by J.W. Cole, Deputy Surveyor, in 1923, from the original BTs, monumented with a ¾" Iron rod, firmly set, 1" above ground, from which the orig. bearing trees

An Oak 25" dia., bears N.70°E., 294 lks. dist, with a healed blaze. (Rec. distance, 275 lks.)
A fallen & rotted Oak 23" dia., bears S.3°E., 420 lks. dist., with an opened and rotted blaze.
An Oak 32" dia., bears S.4¾°W., 353 lks. dist., (slope dist. 360 lks.) with BT visible on an opened and rotted blaze. (Rec. brg. & dist. S.5°W., 360 lks.)
and county surveyors bearing object
A boulder, 3x3.2 ft. above ground, with an X chiseled on top, bears S.36½°E., 75 lks. dist.

At the corner point
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T25S R7W
S 5|S 4
S 8|S 9
1958

from which

- A W.Oak 23" dia., bears N.57 $\frac{3}{4}$ °E., 349 lks. dist., mkd. T25S R7W S4 BT.
- A W.Oak 17" dia., bears S.4 $\frac{1}{4}$ °E., 198 lks. dist. mkd. T25S R7W S9 BT.
- A W.Oak 17" dia., bears S.3 $\frac{1}{4}$ °W., 235 lks. dist., mkd. T25S R7W S8 BT.
- A boulder, 5x5.5 ft. above ground, bears N.22 $\frac{3}{4}$ °W., 151 lks. dist., mkd. X.

Deposit county surveyor's iron rod alongside iron post. Corner falls on a spur, slopes S.5°W.

Fd. & used on BLM dependent resurvey by Bryan S. Seibold & Wayne Rogers, Cadastral Surveyors, under Group #1862, surveyed Sept.-Dec. 1997 - (DCSO records Vol. 53 Page(s) 20303-4)

2