

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 33; & 4 of T26-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, under Contract #57 dated April 12 1855 (DCSO records, Volume 9 Page 3856)

-----  
Marked a Fir, 10" dia., for ¼ sec. post, from which  
A Laurel 24" dia., bears S.60°W., 28 lks. dist.  
A Fir 12" dia., bears N.80°W., 30 lks. dist.

GLO survey by S.C. and A.R. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 9 Page 3900)

-----  
¼ post not found, witness trees found. Made and set Cedar Post, 3 ft. long, 3" sq., from which  
A Laurel 24" dia., bears S.60°W., 28 lks. dist.  
A Fir 12" dia., bears N.80°W., 30 lks. dist.

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June 14, 1966 - C.S. File 54/10-6

-----  
Found - Orig. 24" now 33" Laurel S.60°W., 18.5 ft., prev. opened, upper face rotted away. Open lower & find "B" scribed, reverse.  
Orig. 12" now 30" Fir N.80°W., 19.8 ft., shows very old scar & renovation scar.  
Set Brass cap 2.0 ft. NW of fence corner, course E & S, mkd:  
County Surveyor's Office T25S R7W ¼ S 33  
1966 T26S S 4  
New BTs - 14" D.Fir S.9½°W., 27.0 ft. mkd: S4 CS BT.  
6" W.Fir N.47°W., 33.9 ft. mkd: ¼ S33 CS BT.  
Corner lies approx. 100 ft. W. of small draw, course S. E.