

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3907)

-----  
Set Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 24" dia., bears N.34°W., 13 lks. dist., mkd. ¼ S BT.  
A Cedar 30" dia., bears S.85°W., 50 lks. dist. mkd. ¼ S BT.

BLM resurvey by Lynn Roseberry under Group #645 - Survey, July 1967/Sept. 1968 DCSO records, Volume 36 Page 14968)

-----  
The ¼ sec. cor., determined at record bearing and distance from the original bearing tree:  
A Cedar 53" dia., bears S.85°W., 50 lks. dist., with a healed blaze.

At the corner point  
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 25 S R 7 W  
¼  $\frac{S\ 28}{S\ 33}$   
1968

from which a new bearing tree  
A Fir 13" dia., bears N.28°W., 31 lks. dist., mkd. ¼ S28 BT.

The corner falls at SW. corner of logged area.

Found OK by D. Edwards, Feb. 2004 - M144-13