

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 21 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under Contract #202 dated March 11, 1874 (DCSO records, Volume 9 Page 3891)

-----

Set Cedar post for ¼ sec. cor. from which  
A Fir 8" dia., bears S.24°W., 31 lks.  
A Fir 6" dia., bears N.38°W., 6 lks.

BLM resurvey by Lynn Roseberry, under Group #645, Survey, July 1967/Sept. 1968 - (DCSO records, Volume 36 Pages 14971-72)

-----

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:  
A Fir 20" dia., bears N.38°W., 6 lks. dist., with scribe marks 4 S visible on opened blaze.

At the corner point  
Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 25 S R 7 W

¼  $\frac{S \ 21}{S \ 28}$   
1968

from which new bearing trees  
A Cedar 10" dia., bears N.29½°W., 55 lks. mkd ¼ S21 BT.  
A Fir 32" dia., bears S.19½°E., 62 lks. mkd. ¼ S28 BT.

Fd. Ok by David Edwards, July 2001 - M138-39

Found OK by D. Edwards, Feb. 2004 - M144-13