

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3880)

Set 1/4 sec. post, from which
A Laurel 18" dia., bears S.88°E., 162 lks.
A Fir 24" dia., bears N.87°W., 195 lks.

J.W. Cole - Wit: H. Streese; John harding; Ed Mosher
Jan. 29, 1930 - Volume 3 Page 179

I renewed this corner from the original BTs which were both alive and standing but bearing no scribe marks. I set a 4 x 4 x 36" Oak post, and remarked the old trees "1/4 S CS BT" Both trees checked with government field notes.

BLM resurvey by Irving Zirpel, under Group #411 dated August 1958 (DCSO records, Volume 29 Page 12403)

The 1/4 sec. cor., perpetuated and recorded by J.W. Cole, Deputy Co. Surveyor, in 1930, from the orig. BTs, monumented with an I.P. 1" dia., firmly set, 12" above ground, from which the original trees:

- A Fir 65" dia., bears N.87°W., 200 lks. (196 lks. to the face), re-bark scribed 1/4 SC BT. (Rec. dist. 195 lks)
- A Madrone 25" dia. bears S.88°E., 165 lks. with illegible scribe marks on opened blaze (Rec distance, 162 lks)

At the corner point
Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd: T25S R7W

1/4 S 4
S 9
1958

from which
A Fir 25" dia., bears N.53/4°W., 66 1/2 lks., mkd. 1/4 S4 BT.
A Fir 27" dia., bears S.18 1/2°E., 33 1/2 lks., mkd. 1/4 S9 BT.
Deposit county surveyors I.P. alongside iron post.

Ronald Rice - For: Roseburg Resources Co - Jan 2011 - M162-1

Found - 1958 BLM brass cap with the following accessories:
70" D.Fir bears N.87°W., 132.0' - bark scribing visible
31" Madrone bears S.88°E., 108.9' - rotted face
37" D.Fir bears N.5 3/4°W., 43.9' - healed face
28" D.Fir bears S.18 1/2°E., 22.1' - healed face