

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 343700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. Sec. 33 only, T.2407

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - BLM survey by Jelley and Rogers, under Group #998 Survey, Oct./Nov. 1979 (DCSO records, Volume 43 Pg. 16654)

-----  
Point for the 1/4 sec. cor. of sec. 33 only, at midpoint in departure on the S. bdy. of sec. 33.  
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 24 S R 7 W  
    1/4 S 33  
T 25 S R 7 W  
    1979

from which

- A Fir 16" dia., bears N.10°E., 29½ lks. dist., mkd.  
    1/4 S33 BT.
- A Fir 22" dia., bears N.30°W., 12½ lks. dist., mkd.  
    1/4 S33 BT.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2300 surveyed May 2006 - (DCSO records BLM Plat 2011-2 & Vol. 57 Page(s) 22690)

[www.co.douglas.or.us./survmaps/CORNERS/Cadastral/Plats/2407W](http://www.co.douglas.or.us./survmaps/CORNERS/Cadastral/Plats/2407W)

-----  
As per described by Jelley & Rogers in 1979