

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #63 dated
March 22, 1856 (DCSO records, Vol. 9 Page 3866)

Set post corner for secs. 27, 28, 33 and 34, from which
A Laurel 15" dia., bears N.20°W., 46 lks.
A Maple 9" dia., bears S.40°E., 62 lks.
A Fir 12" dia., bears S.3°W., 79 lks.
A Fir 12" dia., bears N.84°E., 200 lks.

GLO resurvey by Wm. P. Heydon - under Contract #656 dated
May 21, 1896 (DCSO records. Vol. 9 Pages 3905-06)

The sec. cor., which is a white Oak post, set by the County
in place of original corner, from which the original witness
trees bear as follows:

A Fir 18" dia., bears N.84°E., 200 lks. dist., marks
overgrown.
A Maple 16" dia., bears S.40°E., 62 lks. dist.,
marks overgrown.
A Fir 12" dia., bears S.3°W., 79 lks. dist., marked
T25S R7W BT.
A laurel 18" dia., bears N.20°W., 46 lks. dist.,
marks overgrown.

Bureau of Land management resurvey by Lynn Roseberry, under
Group #645, Survey July 1967/Sept. 1968 (DCSO records, Vol. 36
Pages 14958-59)

The sec. cor., determined at record distance from the original
bearing trees:

A Fir 45" dia., bears N.84°E., 200 lks.
dist., with no scribe marks visible on opened blaze.
A Maple 21" dia., bears S.36°E., 62 lks. dist.,
with no scribe marks visible on opened blaze.
(Record, S.40°E.)
A Fir 50" dia., bears S.1°W., 79 lks. dist., with no
marks visible. (Record S.3°W.)
A Madrone 22" dia., bears N.21°W., 46 lks. dist., with no
scribe marks visible on partially opened blaze.
(Record, N.20°W.)

At the corner point

Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the
ground, with brass cap mkd: T 25 S R 7 W

S 28|S 27

S 33|S 34

1968

(Cont Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A Fir 35" dia., bears S.65°E., 46 lks. dist., mkd.
T25S R7W S34 BT.
A Fir 29" dia., bears N.24°W., 80 lks. dist., mkd.
T25S R7W S28 BT.

Found OK by D. Edwards, Feb. 2004 - M144-13