

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #63 dated
March 22, 1856 (DCSO records, Vol. 9 page 3867)

Set ¼ sec. post, from which
A Fir 24" dia., bears N.64°W., 12 lks.
A Fir 15" dia., bears N.22°E., 22 lks.

BLM resurvey by Lynn Roseberry, under Group #645, Survey,
July 1967/Sept. 1968 (DCSO records, Vol. 36 Pgs 14960/61)

Point for the ¼ sec. cor., restored by the method of broken
boundaries; there is no remaining evidence of the original
corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd: T 25 S R 7 W

¼
S 28|S 27
1968

from which
A Fir 8" dia., bears S.31°E., 34 lks. dist.,
mkd. ¼ S27 BT.
A Fir 12" dia., bears N.77°W., 18 lks. dist.,
mkd. ¼ S28 BT.

Found OK by D. Edwards, Feb. 2004 - M144-13