TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 15 and 16

Alias Description
Alias Description
Alias Description
Alias Description

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3877)

Set ¼ sec. post, from which
A Chinquapin, 18" dia., bears N.20°W., 20 lks.
A Fir 24" dia., bears N.10°E., 90 lks.

Percy C. Armstrong - March 24, 1949 - C.S. File 40/227

Run S.10°W., 90 lks. from trunk of Fir tree which answers description of BT.
I drove a 1" x 60" Pipe, and mkd. the following trees:
24 Red Fir N.65°W., 22.0 ft.
6" W.Fir S.10°E., 6.0 ft.
18" W.Fir S.56°E., 47.0 ft.
See File 40/227 for method of setting before using corner.

BLM resurvey by Lynn Roseberry, under Group #645 - Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Pgs. 14965-66)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 25 S R 7 W

¼
S 16|S 15
1968

from which
A W.Fir 11" dia., bears N.21°E., 27 lks. mkd. ¼ S15 BT.
A Fir 6" dia., bears S.52¾°W., 19½ lks. mkd. ¼ S16 BT.

Fd. OK, Greg Lang, October 1989, M 109-3
Fd. OK, Glenn Baughman, January 1992, M 112-43
Fd. Ok by D. Edwards, 11/2005 M149-21
Fd. BC & 2 BTs by C Sweeden, 4/2013 - M165-11
Fd. as per M165-11 by C Sweeden, 10/2015 - M170-14