

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Pages 3878-79)

Set ¼ sec. post, from which
 A Fir 18" dia., bears S.75°W., 43 lks.
 An Oak 12" dia., bears N.65°E., 44 lks.

Doug. County Surveyors Office - James Byron, County Surveyor; M. Godfrey; S. Bilow - Nov. 1957/May 1958 - C.S. File 49/76-8

Found - Orig. 12" now 24" B.Oak stump N.65°E., 29.0 ft. Center rotted near base. Inside I find good scribing "BT" negative.
 36" Fir that checks record bearing & distance for orig. SW BT. I cannot find any scribe marks. Tree has been burned.

Set Brass cap at cor. mkd: ¼ S9|S10 T25S R7W County Surveyors Office, 1957.

Note: I find 2" I.P. 2 ft. above ground that bears S.54½°W., 20.7 ft. Mr. League says I.P. set by Boyer.
New BTs - 10" R.Fir bears S.3½°E., 44.9 ft. scribed ¼ S10 CSBT
 6" R.Fir bears N.19°W., 5.7 ft. scribed ¼ S9 CSBT.

BLM resurvey by Irving Zirpel, under Group #411 - Survey, Sept/Oct. 1958 (DCSO records, Volume 29 Page 12399-40)

The ¼ sec. cor., perpetuated and recorded by Byron DCS in 1958, with an iron pipe 1" dia., 10" above ground, firmly set, at record bearing & distance from two orig. bearing trees, with brass cap; from which the orig. bearing trees:

 A W.Oak snag 28" dia., bears N.65°E., 44 lks. dist., with the overgrowth of the BT visible on the inside of the rotted stump.

 A Fir 54" dia., bears S.75°W., 43 lks. dist., no scribe marks visible. A large hole at the base of the tree gives excessive measurement to the diameter.

and locally established bearing trees:

 A W.Fir 12" dia., bears S.3¾°E., 67 lks. dist., mkd. ¼ S10 CS BT on a double blaze.

 A W.Fir 8" dia., bears N.21¼°W., 9 lks. dist., mkd. ¼ S9 CS BT on a double blaze.

At the corner point

Set a Iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd:

(Cont. Next page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

$\frac{1}{4}$
S 9 | S 10
1959

Deposit County Surveyor's material alongside iron post.
From this point an iron pipe 2½" dia., firmly set, 12"
above ground, bears S.53°W., 31½ lks. dist.