

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3926)

-----  
Mark cross (X) 1 ft. long on a large rock at this point for 1/4 sec. cor., from which

A Cross (X) cut in rock, bears N.10°E., 8 lks.

A Cross (X) cut in rock, bears N.28°W., 210 lks.

No living trees within limits, pits or mound impracticable owing to the steep and stony condition of the surface.

BLM resurvey by Irving Zirpel, under Group #411 dated August 1958 - Survey, 1958 (DCSO records, Volume 29 Pgs 12401-02)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd:

T25S R7W

1/4

S 4 | S 3

1958

from which

A Cedar 15" dia., bears N.29°E., 51 lks. mkd. 1/4 S3 BT.

A Fir 22" dia., bears N.45°W., 71 lks., mkd. 1/4 S4 BT.

Corner falls on a spur, sloping S.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21590)

-----  
the 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2 1/2" dia., firmly set, projecting 1" above ground, in a loose mound of stone, with brass cap (properly) mkd.

from which bearing trees mkd. by Zirpel

A cedar, 28" dia. bears N.29°E. 33.7 ft. w/a healed blaze

A fir, 28" dia., bears N.45°W., 46.9 ft., with scribe marks 1/4 S4 BT visible on a partially healed blaze.

Ronald Rice - For: Roseburg Resources Co. - Jan 2011 - M162-1

-----  
Found - 1958 BLM brass cap with the following accessories:  
31" I.Cedar bears N.29°E., 33.7' - healed face

28" D.Fir bears N.45°W., 46.9' - scribing visible

New BTs - 26" Madrone bears N.5°W., 23.4' - Blazed, scribed "1/4 S4 BT"

25" D.Fir bears S.2°E. 5.1' - blazed, scribed "1/4 S3 BT"

