

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T.24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Wm. R. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3255)

-----  
Intersect S. bdy of the Tp., (T24S R7W), 3.14 chs. E. of cor. to secs. 3 and 4; at which point, I set a post, 4 ft. long, 4" sq., 24" in the ground for closing corner to secs. 33 & 34, marked C C T24S R7W on N.; S34 on E.; and S33 on W.; with 3 notches on E and W sides, from which

A Fir 24" dia., bears N.61°E., 64 lks. dist., mkd.  
T24S R7W S34 BT.

A Fir 15" dia., bears N.20°W., 37 lks. dist.,  
Mkd. T24S R7W S33 BT.

A Fir 12" dia., bears S.1°30'W., 7 lks. dist., mkd.  
T24S R7W CC S33 and 34 BT.

BLM survey by Irving Zirpel, Group #411, Survey, 1958  
(DCSO records, Volume 29 Page 12402)

-----  
Original closing corner of secs. 33 and 34, which has been perpetuated with an iron bar, 1/2" dia., firmly set, 8" above ground, at record bearing and distance from 2 original bearing trees, as follows:

A sawed Fir stump 32" dia., bears N.61°E., 64 lks.  
dist., with a healed blaze.

A Fir 17" dia., the southeasterly of a double fir, bears  
N.20°W., 37 lks. dist., with healed blaze.

Doug. County Surveyors Office - John Powell; J. Heritage  
December 14, 1970 - C.S. File 56/34

-----  
Found - 5/8" Iron rod set firmly at sec. cor.  
Fir stump N.61°E., 42.2 ft. shows good scar.  
17" D.Fir now 19" N.20°W., 24.4 ft. shows good scar.

I do not open trees as every thing fits as noted.

New BT - 32" D.Fir N.21°E., 58.7 ft. scribed T24S R7W S34 CC  
CS BT.

Bruce Shaner, for: Bureau of Land Management - December 11,  
1972 - M 49-7

-----  
Found - 3/4" x 18" Iron rod.  
18" orig. D.Fir, snag, face visible, beas N.20°W.,  
24.4 ft. (to face)

(Cont. Next Page)


PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T.24-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

32" D.Fir scribe visible, bears N.21°E., 58.0 ft.  
28" orig. D.Fir snag, face visible bears N.61°E.,  
42.2 ft.  
Set - Brass cap mkd. "T24S R7W WM S33 S34 CC 1972.  
Note - Tie to secs. 3 & 4, T25-7, S.89°00'E., 204.61 ft.  
(3.10 chs.) (Record East, 207.24 ft., 3.14  
chs.)

Bureau of Land Management resurvey by Berry & Akin under  
Group #807 - Survey, 1973 (DCSO records, Volume 37 Pages  
15295-96)

-----  
At true point for closing cor. of secs. 33 and 34  
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the  
ground, with brass cap mkd:



from which  
A Fir 10" dia., bears N.37°E., 192½ lks., mkd. T24S R7W  
S34 CC BT.  
A Fir 8" dia., bears N.43½°W., 126½ lks., mkd. T24S R7W  
S33 CC BT.

From this point, the original closing corner of secs. 33 and  
34 bears S.0°12'E., 0.075 chs. dist., perpetuated and recorded  
by Bruce Shaner Registered Engineer No. 4906, in 1972,  
monumented with an iron post, 1½" dia., firmly set, protruding  
10" above ground with brass cap. From which remains of the  
original bearing trees

- A sawed fir stump 32" dia., bears N.61°E., 64 lks., with  
a healed blaze.
- A twin Fir snag 17" dia., bears N.20°W., 37 lks., with  
healed blaze.

Add marks AM 1973 to brass cap.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral  
Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 -  
(DCSO records Vol. 55 Page(s) 21588-9)

-----  
The closing cor of secs 33 & 34 only, on the S bdy of T24S R7W  
monumented with an iron post, 2½" dia., firmly set, projecting  
8" above ground, with (1973) brass cap (properly) mkd  
from which bearing trees mkd. by Berry and Akin

- A fir, 23" dia., bears N.37°E., 127.0 ft., with a healed  
blaze.

continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 403700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T.24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 20" dia., bears N.43½°W., 83.5 ft., with a healed blaze.  
and new bearing trees  
A fir, 15" dia., bears N.35¼°E., 44.9 ft., mkd. T24S R7W CC S34 BT.  
A cedar, 6" dia., bears N.34½°W., 20.3 ft., mkd. T24S R7W CC S33 BT.  
From this point, the original closing cor. of secs. 33 and 34 bears S.0°53'00"W. (record, S.0°12'E.), 4.95 ft., perpetuated by the Douglas County Surveyor's Office, in 1970, and Bruce Shaner, Registered Engineer No. 4906, in 1972, monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground, with (1972) brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A sawed fir stump, 31" dia., bears N.61°E., 42.2 ft. with a healed blaze and axe marks visible in the bark.  
A double trunk fir snag, 17" dia., bears N.20°W., 24.4 ft., with no marks visible.  
and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office  
A fir snag, 36" dia., bears N.21°E., 57.8 ft., with scribe marks T24S R7W S34 CS BT visible on a partially healed blaze.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2300 surveyed May 2006 - (DCSO records BLM Plat 2011-2 & Vol. 57 Page(s) 22690)  
[www.co.douglas.or.us./survmaps/CORNERS/Cadastral/Plats/2407W](http://www.co.douglas.or.us./survmaps/CORNERS/Cadastral/Plats/2407W)  
-----  
As per described by Skeesick in 2004