

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3879)

Set 1/4 sec. post, from which
 A Fir 15" dia., bears N.60°E., 70 lks.
 A Fir 15" dia., bears S.45°W, 35 lks.

BLM resurvey by Irving Zirpel, under Group #411 dated 1958 Survey, 1958 (DCSO records, Volume 29 Page 12401)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

 T25S R7W
 S 3
 1/4 S 10
 1958

from which
 A Cedar 23" dia., bears North 10 lks. dist., mkd.
 1/4 S3 BT.
 A Fir 30" dia., bears S.63°W., 106 lks. dist.,
 mkd. 1/4 S10 BT.