TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 and 35

Alias Description
Alias Description
Alias Description
Alias Description

Original - Dennis Hathorn, Deputy, Contract #63 dated March 22, 1856 (DCSO records, Vol. 9 Page 3862)

Set ¼ section post, from which
A B.Oak 30" dia., bears N.57°W., 900 lks.
A W.Oak 12" dia., bears S.6°E., 1120 lks.

Bureau of Land Management resurvey by G. Popken, under Group #869 - Survey May/July 1975 (DCSO records, Vol. 37 Page 15304)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½ ins. dia., 42" in the ground, with top 14" below surface, with brass cap mkd. T 25 S R 7 W

1/4
S 34|S 35
1975

from which
A B.Oak 13" dia., bears N.21½°E., 357 lks. mkd. ¼ S35 BT.
A B.Oak 20" dia., bears N.53½°W., 570 lks. mkd. ¼ S34 BT.
Corner is located in open pasture land.

FD. Ok by D. Edwards, 7/2006 - M151-13
Fd. as per record 4/2018 - by D. Edwards M174-20