

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #63 dated March 22, 1856 (DCSO records, Vol. 9 Page 3865)

Set Post corner, secs. 14, 15, 22 & 23, from which
A W.Oak 9" dia., bears N.25°E., 33 lks.
A W.Oak 10" dia., bears S.30°E., 35 lks.
A W.Oak 15" dia., bears S.25°W., 53 lks.
A W.Oak 10" dia., bears N.55°W., 62 lks.

A. Boyer, Deputy - Hap. Oliver; Dude Powell - Jan. 19, 1944
(No source record found)

Reset from one O.B.T., W.Oak, N.55°W., 62 lks.
New BTs - 15" W.Oak N.21½°W., 58 lks.
18" Cedar S.65½°W., 34 lks.
24" Laurel S.66°E., 2 lks.
Set post at corner.

Doug. County Surveyors Office - James W. Byron; Milo Godfrey;
Clete Putnam - Oct. 26, 1959 - C.S. File 49/76-13

Found - Oak Stake, not scribed, at corner.
W. Oak now 13", N.55°W., 40.9 ft. Old face shows dim
scribing "R7W S15".
15" W.Oak, dead, N.21½°W., 38.3 ft., scribed "CS".
20" Cedar S.65½°W., 22.4 ft. scribed "S22 CS BT".
24" Laurel, down & decaying rapidly, N.66°E.,
instead of S.66°E., 1.3 ft.

Set Iron pipe w/brass cap at cor., mkd. "County Surveyor's
Office, 1959, T25S R7W S 15 | S 14
S 22 | S 23

Blaze & Scribe new trees as follows:
8" D.Fir N.4½°W., 33.7 ft. scribed "T25S R7W S15 CS
BT".
8" I.Cedar N.78°E., 29.7 ft. scribed "T25S R7W
S14 CS BT".
24" D.Fir S.56½°E., 31.4 ft. scribed "T25S R7W S23
CS BT".

Fd. & tied by Roseberry, BLM resurvey, July 1967/Sept. 1968
(DCSO records, Vol. 36 Pages 14956-57)

Found OK July 1993 - R.Dolan, M117-69.
Found OK Feb. 1996 - K.Degroot, M 124-3

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 3/10/1998 - C.S. File 66/2-1

-
- Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 6" above a mound of sand stone. 1959
- 10" now 13" dia., 2 ft. high Oak stump, with illegible scribing visible bears N.55°W., 40.9 ft. (Agrees with rec.) OBT
- 18" now 24" dia., 2 ft. high Cedar stump, with a partially healed blaze, bears S.65½°W., 22.4 ft. (Agrees with rec.) 1944 - (Illegible scribing visible on blaze.)
- 8" now 24" dia., 2 ft. high D.Fir stump, with a fully healed double blaze, bears N.4½°W., 33.7 ft. (Agrees with rec.) 1959
- 8" now 19" dia. I.Cedar with a fully healed double blaze, bears N.78°E., 29.7 ft. (Agrees with rec.) 1959
- 24" now 32" dia., 2 ft. high D.Fir stump with a healed blaze, bears S.56½°E., 31.4 ft. (Agrees with rec.) 1959
- New BTs- 7" D.Fir, double blazed and scribed "T25S R7W S23 CS BT" bears S.8°E., 13.8 ft.
- 8" D.Fir, double blazed and scribed "T25S R7W S15 CS BT" bears N.26°W., 11.3 ft.