

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated
June 8, 1857 (DCSO records, Vol. 9 Page 3875)

Set 1/4 sec. post, from which
 A Fir 15" dia., bears N.70°E., 19 lks.
 A Cedar 12" dia., bears N.28°W., 42 lks.

Bruce Shaner, For: U.S. BLM - Oct. 27, 1972 - M 49-1

Set - Brass cap mkd: T25S, R7W, WM 1/4 S15|S14 1972.
Found - 36" orig. D.Fir BT stump with scribes visible bears
 N.70°E., 12.5 ft.
New BTs - 14" D.Fir "1/4 S15 BT" bears S.62°W., 18.0 ft.
 36" D.Fir, stump, "1/4 S14 BT" bears S.31 1/2°E., 29.9'.

Found OK, March 1994 by R. Dolan - M118-74.
Found OK, Feb. 1996 by K. DeGroot - M 124-3

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert H. Browning, Surveying Tech under Group
#1905, surveyed April/May 1999. (DCSO Vol. 53 pgs 20621-2 &
Vol. 55 Pgs 21825-6 Amended)

The 1/4 sec. cor. of secs. 14 & 15, perpetuated by Shaner in
1972, subsequently recovered and utilized by Dolan, in 1994,
recovered and utilized by DeGroot, in 1996, monumented with an
iron post, 1 1/4" dia., firmly set, projecting 8" above the
ground, with a 2 1/2" brass cap mkd. T 25 S R 7 W
 1/4
 S 15 | S 14
 1972

from which the remains of an original bearing tree
 A sawed & decayed fir stump, 36" dia., bears N.70°E.,
 12.5 ft. scribe marks BT visible.
and bearing trees mkd. by Shaner
 A sawed fir stump, 48" dia., bears S.27 1/2°W., 29.5 ft.
 with a healed blaze.
 A fir, 22" dia., bears S.63 1/2°W., 17.6 ft. with a healed blaze.
and a new bearing tree
 A cedar, 8" dia., bears N.35 3/4°E., 17.0 ft. mkd. 1/4 S14 BT.
From the cor. point, an iron pipe 3/4" diam., firmly set
projecting 24" above the ground, bears N.54°46'15"E., 5.8 ft.
dist. The purpose and origin of this monument is unknown and
it was not utilized in the course of this survey.

Fd. Ok by D. Edwards, 11/2005 M149-21
Fd. BC, 4 BTs (2 stumps) & 3/4" IP by C Sweeden, 4/2013 - M165-11
Fd. as per M165-11 by C Sweeden, 10/2015 - M170-14