

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3876)

Set post on Summit of mountain, for cor. secs. 2, 3, 10 and 11, from which

- A Fir 24" dia., bears S.10°E., 18 lks.
- A Fir 36" dia., bears N.45°W., 11 lks.
- A Fir 12" dia., bears S.75°W., 34 lks.
- A Fir 12" dia., bears N.88°E., 50 lks.

BLM resurvey by Irving Zirpel, under Group #411 dated August 8, 1958. Survey, 1958 (DCSO records, Volume 29 Pages 12394-95)

Point for the sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T25 S R7W
S 3 | S 2
S 10 | S 11
1958

from which

- A W.Fir 24" dia., bears N.39½°E., 31 lks. dist., mkd. T25S R7W S2 BT.
- A W.Fir 18" dia., bears S.10°E., 9 lks. dist., mkd. T25S R7W S10 BT.
- A W.Fir 15" dia., bears S.56°W., 58½ lks. dist., mkd. T25S R7W S10 BT.
- A W.Fir 23" dia., bears N.54°W., 103 lks. dist., mkd. T25S R7W S3 BT.

Doug. County Surveyors Office - Milo Godfrey; Vernon Tracy; Clete Putnam - Jan. 17, 1962 - C.S. File 49/76-19

Found - 24" W.Fir stump, 6 ft. high, N.39½°E., 20.5 ft.

18" W.Fir snag S.10°E., 5.9 ft.

15" W.Fir snag S.56°W., 38.6 ft.

23" W.Fir N.54°W., 68.0 ft. This tree still alive but broken off about 20 ft. above ground.

All BTs dead but one. All scribing visible on BTs.

Brass cap pulled out by uprooted tree, set in 1958.

Reset Brass cap in original position.

New BTs - 6" D.Fir S.16°E., 33.0 ft. mkd. T25S R7W S11 CS BT.

8" W.Fir S.71½°W., 45.8 ft. mkd. T25S R7W S10 CSBT.

(Cont Next page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

15" W.Fir N.58°W., 70.5 ft. mkd. T25S R7W S3 CS BT. 18" D.Fir, North, 26.4 ft. mkd. T25S R7W S2 CS BT. No trees (alive) available to Northeast.	
Bruce Shaner, For U.S. Bureau of Land Management - Dec. 26, 1972 - Map File M 47-40 -----	
Found -	1958 BLM brass cap. 24" D.Fir N.39½°E., 20.5 ft. High stump with scribes visible. (Record, White Fir) 18" W.Fir S.10°E., 5.9 ft. Badly rotted stump with scribes visible. 15" W.Fir S.56°W., 38.6 ft. Badly rotted stump with scribes visible. 23" W.Fir N.56°W., 68.0 ft. Badly rotted stump with scribes visible.
New BTs -	36" D.Fir stump N.70½°W., 83.3 ft. to face, scribed "T25S R7W S3 BT". 6" D.Fir S.77°E., 40.0 ft. scribed "T25S R7W S11 BT" 10" W.Fir S.3°W., 24.7 ft. scribed "T25S R7W S10 BT"
Ronald L. Rice, Ward NW - Sept 2010 - C.S. File 65/69-58 -----	
Found -	2½" BLM brass cap dated 1958 with the following accessories: 17" D.Fir bears S.77°E. 40.0' - bark scribing visible 22" W.Fir bears S.30°W. 24.7' - healed face
New -	15" D.Fir bears N.21°W. 9.2' - blazed, scribed "T25S R7W S3 BT" 15" D.Fir bears N.26°E. 7.8' - blazed, scribed "T25S R7W S2 BT"
Note -	Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Compass Declination 16° East
Fd. 1958 BLM BC with all accessories as noted by R.Rice 12/2012 - M164-50	