

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 and 3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3925)

-----  
A Cedar, 24" dia., for ¼ sec. cor. mkd. ¼S on W. side, from which  
    A Cedar 30" dia., bears N.45°E., 50 lks. mkd. ¼ S BT.  
    A Fir 40" dia., bears N.10°W., 25 lks. mkd. ¼ S BT.

BLM resurvey by Irving Zirpel, under Group #411 dated August 1958. Survey, 1958 (DCSO records. Vol. 29 Pg. 12397)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner. Set a Iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top with brass cap mkd:

T25S R7W  
    ¼  
    S 3|S 2  
    1958

from which  
    A Fir 9" dia., bears N.39°E., 96½ lks., mkd ¼ S2 BT.  
    A Hemlock 17" dia., bears S.66°W., 98½ lks., mkd. ¼ S3 BT.

Bruce Shaner, For U.S. BLM - Dec. 26, 1972 - M 47-40

-----  
Found - 1958 BLM brass cap.  
        10" W.Fir N.39°E., 63.7 ft. scribes visible.  
        20" Hemlock S.66°W., 64.0 ft. scribed visible, now down.  
New BT - 12" Yew S.67°W., 48.0 ft. scribed "¼ S3 BT".

Found OK by D. Edwards, Nov. 2001 - M139-10

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21593)

-----  
The ¼ sec. cor. of secs. 2 and 3, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, and in a loose mound of stone, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Zirpel  
    A fir, 17" dia. bears N.39°E. 63.7 ft with a healed blaze  
    A roothole bears S.62½°W., 65.0 ft., with fallen hemlock snag, 20" dia., lying alongside, no marks visible.  
    (Record, S.66°W.)

continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 and 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Bruce Shaner  
A yew, 13" dia., bears S.66 $\frac{3}{4}$ °W., 48.2 ft., with scribe marks  $\frac{1}{4}$  S3 BT visible on a partially healed blaze.

Ronald L. Rice, Ward NW - Rob Ward & Josh Reed - Sept 2010 - C.S. File 65/69-57

-----

Found - 2 $\frac{1}{2}$ " BLM brass cap dated 1958 (pronounced lean to the north, which appears to be the condition in which it was set) with the following accessories:  
18" D.Fir bears N.39°W., 63.7' - healed face  
14" Yew snag bears S.66 $\frac{3}{4}$ °W. 48.2' - scribing visible

New - 14" D.Fir bears N.86°W., 18.6' - blazed, scribed " $\frac{1}{4}$  S3 BT"  
12" D.Fir bears S.55°E., 20.5' - blazed, scribed " $\frac{1}{4}$  S2 BT"

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.  
Compass Declination 16° East