

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T24-7

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Wm. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3228)

 Set a post, 4 ft. long, 4" sq., 24" in the ground, mkd. T24S S35 on NE.; T25S S2 on SE.; R7W S3 on SW.; and S34 on NW faces with 2 notches on E and 4 notches on W edges, from which

A Cedar 16" dia., bears N.49°E., 91 lks. dist., mkd. T24S R7W S35 BT.

A Cedar 18" dia., bears S.81½°E., 54 lks. dist., mkd. T25S R7W S2 BT.

A Fir 30" dia., bears S.27°W., 17 lks. dist., mkd. T25S R7W S3 BT.

A Fir 24" dia., bears N.19°W., 60 lks. dist., mkd. T24S R7W S34 BT.

 BLM resurvey, by Irving Zirpel, Jr., Group #411 - Survey, Sept/Oct. 1958 (DCSO records, Volume 29 Pages 12397-98)

 The cor. of secs. 2, 3, 34 and 35, on N. bdy. of T., which is determined at the intersection of the bearings from the faces of two BTs, which do not match the record, but the bark scribing on these trees is of the same character as that used throughout the Tp. and has the same appearance of scribing established at the same date. This same point has been monumented with a wooden stake, 2x2 ins. cross section, 3 ft. above ground, firmly set. Also there is a very old squared, wooden stake 4x4 ins. cross section lying at this point, no scribe mark visible. I accept this position as the best available evidence of the original corner. From which:

A Fir 36" dia., bears S.66°E., 75 lks. dist., bark scribed T2 R W S BT and other illegible scribe marks.

A Fir 36" dia., bears S.35°W., 71½ lks. dist., bark scribed T25S R7W S BT, the scribing has been separated by a bark split.

and a locally established tree of which I have no record:

A Cedar 25" dia., bears S.71°E., 65½ lks. dist., with scribe marks T W 2 BT visible on opened blaze.

At the corner point: Set a Iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T 24	S R 7 W
S 34	S 35
S 3	S 2
T 25	S

1958

from which

(Cont. Next page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T24-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Cedar 6" dia., bears N.45½°E., 54 lks., mkd. T24S R7W S35 BT.
A Fir 20" dia., bears N.71½°W., 77½ lks., mkd. T24S R7W S34 BT.

Mark Smalley - For: Roseburg Resources - May 2003 - M142-29

Found - 1958 BLM Brass cap on an iron pipe.
40" Fir S.66°E., 49.5' bark scribe not visible.
36" Fir stump S.35°W., 47.2'
25" Cedar S.71°E., 43.2' scribe visible.
20" Cedar N.45½°E., 35.6' healed.
28" Fir N.71½°W., 51.2' healed.
New BTs- 14" W.Fir S.67°E., 2.0' scribed "S2 BT"

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21586-7)

The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap (properly) mkd. from which the remains of BTs mkd. by person(s) unknown, reported by Zirpel
A cedar, 24" dia., bears S.75½°E., 43.2 ft., with scribe marks T W visible on open blaze. (Record, S.71°E)
A fir, 39" dia., bears S.66°E., 49.5 ft., with fragmentary scribe marks visible on a bark blaze.
A sawed fir stump, 40" dia., bears S.33½°W., 45.6 ft. with fragmentary scribe marks visible on a bark blaze. (Record, S.35°W., 47.2 ft.)
and bearing trees mkd. by Zirpel
A cedar, 20" dia., bears N.45½°E., 35.6 ft., with a healed blaze.
A fir, 26" dia., bears N.71½°W., 51.2 ft., with a healed blaze.
and a bearing tree mkd. by Mark F. Smalley, in 2003
A fir, 14" dia., bears S.71°E., 2.0 ft., with scribe marks S2 BT visible on a partially healed blaze.
and a new bearing tree
A hemlock, 11" dia., bears S.78½°W., 45.6 ft., mkd. T25S R7W S3 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

continued next page

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2 & 3; 34 & 35 - T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L. Rice, Ward NW - Rob Ward & Josh Reed - Sept 2010 -
C.S. File 65/69-56

Condition report only

Found - 2½" BLM brass cap dated 1958 with the following accessories:

- 24" Cedar bears S.75½°E. 43.2' - scribing visible
- 40" D.Fir bears S.66°E. 49.5' - bark scribing visible
- 40" D.Fir stump bears S.33½°W. 45.6' - bark scribing visible
- 22" Cedar bears N.45½°E., 35.6' - healed face.
- 28" D.Fir bears N.71½°W., 51.2' - healed face.
- 14" W.Fir bears S.71°E., 2.0' - healed face.
- 12" W.Fir (record Hemlock) bears S.78½°W., 45.6' - scribing visible.

Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.

Compass Declination 160 East