TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias Description
Alias Description
Alias Description
Alias Description

Original - Dennis Hathorn, Deputy, Contract #63 dated March 22, 1856 (DCSO records, Vol. 9 Page 3865_

Set ¼ sec. post, from which
A W.Oak 10" dia., bears N.72°E., 177 lks.
A W.Oak 15" dia., bears N.52°W., 361 lks.
No tree convenient South of corner.

BLM resurvey by Lynn Roseberry, under Group #645 - Survey, July 1967/September 1968 (DCSO records, Vol. 36 Pg. 14956)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 25 S R 7 W

¼ S 14 / S 23
1968

from which
A Fir 9" dia., bears N.30°E., 28½ lks. mkd. ¼ S14 BT.
A Fir 12" dia., bears S.33°E., 38½ lks. mkd. ¼ S23 BT.

Found OK July 1993 - R. Dolan, M117-69
Found OK Feb. 1996 - K. DeGroot, M 124-3

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 3/10/1998 - C.S. File 66/2-4

Found - 3¼" dia., brass cap on a 2½" O.D. iron pipe, protrudes 5" above ground. 1968
9" now 21" dia., D.Fir with a fully healed single blaze, bears N.30°E., 18.8 ft. (Agrees with rec.) 1968
12" now 23" dia. D.Fir with a fully healed single blaze, bears S.33°E., 25.4 ft. (Agrees with rec.) 1968
New BTs - 18" dia., D.Fir, double blazed and scribed "¼ S23 CS BT" bears S.68°W., 20.5 ft.
7" dia., I.Cedar, double blazed and scribed "¼ S14 CS BT" bears N.1½°E., 36.4 ft.

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1905, surveyed April/May 1999. (DCSO rec. Vol. 53 page(s) 20614-5)