

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3924)

90 Ft. below summit of ridge, Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec .cor. marked ¼S on N. face, from which

- A Cedar 16" dia., bears S.39°W., 29 lks. dist. mkd. ¼ S BT.
- A Fir 18" dia., bears N.12°W., 77 lks. dist., mkd. ¼ S BT.

BLM resurvey by Irving Zirpel, under Group #411 dated August 8, 1958. Survey, 1958 (DCSO records, Vol. 29 Pgs. 12395-96)

The ¼ sec. cor., determined at record distance from two orig. bearing trees, as follows:

- A Fir snag, 24" dia., bears N.18¼°E., 77 lks. dist., bark scribed S¼ BT. (Rec. N.12°W.)
- A sawed Cedar stump 36" dia., bears S.54¾°W., 29 lks. dist. with portion of scribe mark B visible on opened blaze, the blaze on this tree faces North. (Rec. S.39°W.)

At the corner point
Set a Iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T25S R7W
¼ $\frac{S \ 2}{S \ 11}$
1958

from which

- A Cedar 14" dia., bears N.12°W., 106½ lks. dist., mkd. ¼ S2 CS BT.
- A Fir 10" dia., bears S.39½°W., 8½ lks. dist., mkd. ¼ S11 CS BT.

From this point, a monument set by the County Surveyor, bears N.51¾°W., 13 lks. dist., an iron post 1" dia., firmly set 6" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T25S ¼ S2 S11 1957.

from which county BTs:

- A Cedar 14" dia., bears N.7°W., 97 lks. dist., mkd. ¼ S2 CS BT.
- A Fir 10" dia., bears S.17½°E., 15½ lks. dist., mkd. ¼ S11 CS BT.

(Cor. set by Byron & crew in 1957. Removed corner to agree with Cadastral survey. May 14, 1959) See C.S. File 49/76-12)

Found OK by D. Edwards, Nov. 2001 - M139-10

cont.

