

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

David Edwards - For: Roseburg Resources - Nov. 2001 - M139-10

Set - 5/8"x48" steel pin w/alum. cap mkd. per 1973 Manual & "L.S. 2339" and "2001".
A 21" Fir bears N.43°E., 19.2'
A 4" Fir bears S.36°30'E., 25.3'
A 9" Fir bears S.40°W., 11.3'
A 13" Fir bears N.73°W., 6.1'
These new BTs are all scribed "C ¼ S2 BT" and measured to center of tree at root crown.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21591-2)

The center ¼ sec. cor. of sec. 2, established by Edwards, in 2001, and is accepted as the cor., monumented with an iron rod, 5/8" dia., firmly set, projecting 10" above ground, with alum. cap (properly) mkd.
from which the bearing trees mkd. by Edwards
A fir, 22" dia., bears N.48¼°E., 19.4 ft., with scribe marks ¼ S2 BT visible on a partially healed blaze.
A fir, 5" dia., bears S.37¼°E., 25.4 ft., with scribe marks C¼ S2 BT visible on a partially healed blaze.
A fir, 9" dia., bears S.43¾°W., 11.6 ft., with scribe marks C¼ S2 BT visible on a partially healed blaze.
A fir, 14" dia., bears N.69½°W., 6.2 ft., with scribe marks C¼ S2 BT visible on a partially healed blaze.