

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #63 dated March 22, 1856 (DCSO records, Vol. 9 Page 3861)

-----  
Set ¼ sec. post, from which  
    A B.Oak 12" dia., bears S.28°W, 24 lks.  
    A B.Oak 12" dia., bears N.69°E., 124 lks.

Doug. County Surveyors Office - James Byron, Deputy - M. Godfrey; S. Bilow - April 10, 1958 - C.S. File 49/76-1

-----  
Found - Both original BTs.  
        The NE BT, now down, has open face, good scribing ¼S.  
        The SW BT now snag, I open & find good scribing "¼S BT".  
        Both BTs check for bearing and distance.  
        The SW BT recorded 12" B.O., we find it to be 24" when scribed.  
Set Brass cap at cor. mkd: ¼ S23|S24 T25S R7W County Surveyors Office, 1958.  
New BTs - 9" R.Fir bears S.81°E., 15.0 ft. scribed ¼ S24 CS BT.  
          16" R.Fir bears S.80°W., 18.5 ft. scribed ¼ S23 T25S R7W CS BT.

Found OK July 1993 - R. Dolan, M117-69.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/9/98 - C.S. File 64/79-24

-----  
Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground. 1958  
        No OBTs found.  
        1958 SE BT now gone.  
        16" now 20" dia., dead D.Fir with a fully healed double blaze, bears S.80°W., 18.5 ft. (Agrees with rec.) 1958  
New BTs - 13" dia. Madrone, double blazed and scribed "¼ S23 CS BT" bears S.73°W., 15.2 ft.  
          13" dia. D.Fir, single blazed and scribed "¼ S23 CS BT" bears S.56°W., 3.5 ft.  
          10" dia. Madrone, double blazed and scribed "¼ S24 CS BT" bears S.41½°E., 26.4 ft.  
          15" dia. B.Oak, double blazed and scribed "¼ S24 CS BT" bears N.21°E., 47.4 ft.  
Note - Cat road is 15 ft. south of corner. See sketch in file.