

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3921)

Set Cedar post, 3 ft. long, 4" sq., 24" in the ground for the sec. cor. and marked T25S S1 on NE.; R7W S12 on SE.; S11 on SW and S2 on NW faces with 5 notches on S and 1 notch on E. edges, from which:

- A Cedar 36" dia., bears N.30°E., 130 lks. dist. mkd.
T25S R7W S1 BT.
- A Fir 40" dia., bears S.53°E., 72 lks. dist., mkd.
T25S R7W S12 BT.
- A Fir 24" dia., bears S.55°W., 76 lks. dist., mkd.
T25S R7W S11 BT.
- A Cedar 34" dia., bears N.34°W., 33 lks. dist., mkd.
T25S R7W S2 BT.

R.H. Gee; R.J. Henrikson; S.Danchok; - June 14, 1955
C.S. File 42/24

Found scribed 4"x4"x3' post which was badly burned. Replaced post with a ¾" iron pipe, from which

- A Red Cedar 40" N.30°E., 85.0 ft. (OBT, scribe marks visible.)
- A R.Cedar 38" N.34°W., 21.8 ft. (OBT, marks visible).
- A Fir 50" S.53°E., 47.5 ft. (OBT, marks visible)
- A R.Cedar 10" S.63°W., 55.0 ft., new BT marked
S11 T25S R7W BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.Bilow - 5/1958 C.S. File 49/76-11

Found - Orig. 34" now 46" Cedar. I open & find good scribing T25S R7W S2 N.34°W., 21.8 ft.
Orig. 40" now 50" R.Fir shows fair bark scribing "S W T B" (Rec. S.53°E. I find should be S.35°E., 47.6 ft. (Dist. OK)
I also find ¾" I.P. set alongside 3"x3"x2'.6" sq. & scribed Post, which seems to be old but definitely not at original position, as I cannot find any decayed wood there.
I do not find any trace of the NE or SW BTs.
Set Brass cap at cor. mkd. $\frac{S\ 2}{S\ 11} \frac{S\ 1}{S\ 12}$ T25S R7W County Surveyor's Office, 1957
Note: I also find 9" Cedar bears S.44°W., 73.6. ft. scribed by R.Gee: T25S R7W S11 BT. I scribe CS on this BT.
(Cont. Next Page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs - 16" Cedar bears S.66°E., 5.0 ft. scribed S12 T25S
R7W CS BT.

12" Cedar bears N.12°E., 29.7 ft. scribed S1 T25S
R7W CS BT.

46" orig. Cedar N.38°W., 22.8 ft. rescribe S2 T25S
R7W CS BT.

3/4" Iron pipe bears S.6°E., 26.2 ft.

Note: On this date, I find original 36" now 48" Cedar. I open
& find good scribing, bears N.15°E., rec. N.30°E., Dist.
checks record 85.8 ft. All BTs face to corner & all distances
check record & one bearing checks. I find no trace of SW BT.
I destroy corner set by Gee in 1955. (C.S. File 42/24-002)

BLM resurvey by Irving Zirpel, under Group #411 dated August
8, 1958 - Survey, 1958 (DCSO records, Volume 29 Page 12395)

The Sec. cor., which has been perpetuated & recorded by J.W.
Byron D.C.S. in 1958, at record dist. from three original BTs
Monumented with a very old wooden stake, 4x4 ins. cross
section 3 ft. long, with scribe marks S1 and other illegible
markings on it (possible original), firmly set alongside an I.
post, 1" dia., firmly set, 8" above ground, with 1957 County
Brass cap.

from which the original bearing trees:

A Cedar 40" dia., bears N.14°E., 130 lks. dist., with
the overgrowth of scribe marks tacked to the tree.
(Rec. bearing N.30°E.)

A Fir 56" dia., bears S.33¾°E., 72 lks. dist., bark
scribed T25S S1 BT. (Rec. S.53°E.)

A Cedar 46" dia., bears N.34°W., 33 lks. dist., with
scribe marks T25S R7W S2 visible on opened blaze.
The tree has been rescribed by the county surveyor,
T25S R7W S2 CS BT.

and county surveyor's bearing trees:

A Cedar 13" dia., bears N.13°E., 44 lks. dist., mkd.
T25S R7W S1 CS BT.

A Cedar 15" dia., bears S.65°E., 7½ lks. dist., mkd.
T25S R7W S12 CS BT.

A Cedar 11" dia., bears S.44°W., 109 lks. dist., mkd.
CS S11 T25S R7W BT.

At the corner point:

Cont next page)

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a Iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd:

T25S R7W
S 2 | S 1
S 11 | S 12
1958

Deposit local cor. material alongside iron post.

Fd. OK - David Edwards - Feb. 1997 - M 126-45 & CS 65/12-3 A&B
Found OK by D. Edwards, Nov. 2001 - M139-10
Fd. 1958 BLM BC by R. Rice 12/2012 - M164-50