

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - William P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3923)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd: 1/4 S on W. face, from which
A Fir 20" dia., bears N.70°W., 20 lks. mkd. 1/4 S BT.
A Fir 24" dia., bears S.89°W., 50 lks., mkd. 1/4 S BT.

BLM resurvey by Lynn Roseberry, under Group #645. Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Page 14955)

Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor. Set a Iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 25 S R 7 W
1/4
S 2 | S 1
1967

from which
A Cedar 32" dia., bears N.73 1/4°E., 147 lks. mkd. 1/4 S1 BT.
A Fir 38" dia., bears S.17 1/4°W., 226 lks., mkd. 1/4 S2 BT.

Found OK by D. Edwards, Nov. 2001 - M139-10

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2079 - Surveyed July/Aug. 2004 - (DCSO records Vol. 55 Page(s) 21592)

The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 2 1/2" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Roseberry
A cedar, 47" dia., bears N.73 1/4°E., 97.0 ft., with a healed blaze.
A sawed fir stump, 42" dia., bears S.17 1/4°W., 149.2 ft., with a healed blaze.

and new bearing tree

A fir, 22" dia., bears N.17°W., 34.5 ft., mkd. 1/4 S2 BT. The geographic position (NAD 1983 (CORS 96)) of the 1/4 section corner of sections 1 & 2, as determined by ties to stations "DODSON BUTTE CORS ARP" & "CAPE BLANCO CORS ARP" is as follows:

Latitude: 43°25'29.82"N.

Longitude: 123°29'08.98"W.

Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base on right side center.