

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36 of T24-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Wm. R. Whipple under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3227)

-----  
 Set a post, 4 ft. long, 4" sq., 24" in the ground, marked T24S S36 on NE.; T25S S1 on SE.; R7W S2 on SW.; and S35 on NW faces with 1 notch on E and 5 notches on W edges, from which

- A Fir 24" dia., bears N.16½°E., 60 lks. dist., mkd. T24S R7W S36 BT.
- A Fir 40" dia., bears S.61°E., 114 lks. dist., mkd. T25S R7W S1 BT.
- A Fir 30" dia., bears S.17°W., 124 lks. dist., mkd. T25S R7W S2 BT.
- A Fir 30" dia., bears N.50°W., 103 lks. dist., mkd. T24S R7W S35 BT.

Bureau of Land Management resurvey by Lynn Roseberry under Group #645, Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Pages 14950-51)

-----  
 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T	24	S	R	7	W	
		S	35		S	36
		S	2		S	1
T	25	S	R	7	W	
					1967	

from which

- A Fir 17" dia., bears N.59°E., 13 lks. dist., mkd. T24S R7W S36 BT.
- A Fir 25" dia., bears S.16¼°E., 57 lks. dist., mkd. T25S R7W S1 BT.
- A Fir 17" dia., bears S.29½°W., 31½ lks. dist., mkd. T25S R7W S2 BT.
- A Fir 43" dia., bears N.50½°W., 183 lks. dist., mkd. T24S R7W S35 BT.

Fd. Ok, by Mark Smalley, 10/94 - C.S. File 63/154-18