

PRIMARY CORNER DESCRIPTION Center 1/4 cor. Sec. 13

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Kristian DeGroot - February 1996 - M 124-3 - for: Henry Bros.

Set - 5/8"x30" I.R. 28" in the ground with a 2" alum. cap stamped:

T25S R7W

C¹/₄ S13

1996

PLS 1941

8" D.Fir, bears S.5°W., 15.9', scribed "C¹/₄ S13 BT".

9" D.Fir, bears N.61°30'E., 13.4', scribed "C¹/₄ S13 BT".

5/8" x 30" I.R., bears N.5°E., 17.76', w/plastic cap mkd. "BTS Eng-Surv".

5/8" x 30" I.R., bears S.61°30'W., 18.10', w/plastic cap mkd. "BTS Eng-Surv".

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1905, surveyed April/May 1999. (DCSO rec. Vol. 53 page(s) 20615-6)

The center ¹/₄ sec. cor. of sec. 13, established by DeGroot, in 1996, is accepted as a careful & faithful determination of the corner; monumented with a 5/8" rebar, firmly set projecting 3" above the ground, with a 2" aluminum cap mkd.

T 25 S R 7 W

C 1/4

S 13

1996

PLS 1941

from which the bearing trees mkd. by DeGroot

A fir, 9" dia., bears N.58³/₄°E., 13.4 ft. with illegible scribe marks visible on partially healed double blaze.

A fir, 8" dia., bears S.2³/₄°W., 15.7 ft. with scribe marks C ¹/₄ S 13 BT visible on partially healed double blaze.

and reference monuments set by DeGroot

A 5/8 in rebar firmly set projection 2" above the ground for a reference monument, bears N.3°43'36"E., 17.8 ft. with aluminum cap mkd. BTS ENG SURV.

A 5/8 in rebar firmly set projection 3" above the ground for a reference monument, bears N.58°43'19"W., 18.1 ft. with aluminum cap mkd. BTS ENG SURV.

From the cor. point, an axle, 1¹/₄" diam., with a 6" diam. hub atop, firmly set, projecting 6" above the ground, bears S.89°46'W., 17.0 ft. The purpose and origin of this monument is unknown and it was not utilized in the course of this survey.