

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Wm. P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Volume 9 Page 3920)

Set a Fir post 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., mkd. 1/4 S on N. face, from which
A Fir 16" dia., bears S.37°E., 80 lks. dist., mkd. 1/4 S BT.
A Fir 14" dia., bears N.9°E., 48 lks. dist., mkd. 1/4 s BT.

Doug. County Surveyors Office - Milo Godfrey; Vernon Tracy; Clete Putnam - March 1962 - C.S. File 49/76-20

Found - Fir tree, 39" S.27°E., (instead of S.37°E) 52.8 ft. This tree has been opened previously & good scribing "1/4S" visible on old face.
31" Fir N.9°E., 31.7 ft. shows very good scar, Did not chop open.

Set Brass cap at cor. mkd: County Surveyor's T25S R7W 1/4 S 12
Office, 1962 S 13

Rescribe- 31" D.Fir N.9°E., 31.7 ft. mkd. 1/4 S12 CS BT, in wood.

New BT - 16" D.Fir S.30°W., 19.3 ft. mkd. 1/4 S13 Cs BT.
Corner lies on W. slope approx. 130 ft. W. of top of ridge.
Also found 32" D.Fir N.45°E., 48.4 ft. with scribing visible in opening previously chopped out. (unrecorded BT)

Found OK, Feb. 1996, by K. DeGroot - M 124-3

Found OK, Feb. 1997, by D. Edwards - M 126-45 & CS 65/12-3A&B