

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - William P. Heydon, under Contract #656 dated May 21, 1896 (DCSO records, Vol. 9 Page 3922)

Set a Cedar post, 3 ft. long, 4" sq. 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Fir 15" dia., bears N.30°E., 47 lks. dist., mkd. 1/4 S BT.

A Fir 12" dia., bears S.26°E., 52 lks. dist., mkd. 1/4 S BT.

R. H. Gee, R. J. Henrikson; S. Danchok - June 14, 1955
C.S. File 42/24-1

Found BT for section 1, tree down but scribe marks 1/4 S1 BT visible.

Reset 1/4 corner according to records, turned bearing to other BT, which is now a stub, no bark.

Corner is a 3/4" Iron pipe, from which bears

A 10" hemlock, S.12°E., 9.3 ft. mkd. 1/4 S12 T25S R7W BT. Placed tag on this tree.

A 12" Hemlock N.53°W., 30.1 ft., mkd. 1/4 S1 T25S R7W BT.

(At a point 276' S. on center line of sec. 12, go N.78°E., 10.0' to 48" Fir, which has several nice marks and "1/4S" carved with knife in bark. No record of this tree. Do not destroy.)

Fd. OK - David Edwards - Feb. 1997 - M 126-45 & CS 65/12-3
A&B