

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T25-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #272, dated August, 1877
(DCSO records, Volume 9 Page 3848)

Set a Fir post, 36" long 4" dia. 1/2 in ground for cor. to
secs. 7, 12, 13 and 18, from which

- A Fir 20" dia. bears N.60°E., 33 lks. dist.
- A Maple 8" dia. bears S.80°W., 35 lks. dist.
- A Fir 16" dia. bears S.28°E., 50 lks. dist.
- A Fir, 60" dia. bears N.68°W., 50 lks. dist.

Wm. P. Heyden, Contract #656 dated May 1896. (DCSO records
Volume 9 Page 3853)

Corner is a Fir post still standing marked and witnessed as
described by the Surveyor General.

Bureau of Land Management, Lynn Roseberry, Group #645 -
Survey July 20, 1967 to Sept. 25, 1968 (DCSO records, Volume
36 Page 14948)

The cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp
determined at record dist. from the remaining orig. BTs:

- A sawed Fir stump, 43" dia. bears N.78¾°E., 33 lks. dist
with no marks visible. (Record, N.60°E.)
- A shattered Fir stump 50" dia. bears S.5°E., 50 lks.
dist. with bottom of orig. blaze visible. (record
S.28°E.)
- A sawed Fir stump 64" dia. bears N.82°W., 50 lks. dist.
with no marks visible. (record, N.68°W.)

At the corner point: set an iron post, 28" long 2½" dia. 18"
in the ground, & in a mound of stone, 3 ft. base, to top,
with brass cap mkd.

T 25 S
R 7 W | R 6 W
S 12 | S 7
S 13 | S 18

1968

from which new BTs:

- A Fir 15" dia. bears N.40°E., 127 lks mkd. T25S R6W S7BT
- A Fir 6" dia. bears S.88°E., 55½ lks. mkd T25S R6W S18BT
- A Fir 6" dia. bears S.50¾°W., 38 lks. mkd T25S R7W S13BT
- A Fir 5" dia. bears N.74°W., 64½ lks. mkd T25S R7W S12BT

FD. OK - David Edwards - Feb. 1997 - M 126-45 & CS 65/12-3A&B