

TOWNSHIP 25 RANGE 07 POINT IDENTIFIER # 700677

PRIMARY CORNER DESCRIPTION Tsp. Cor. (NW Cor. Sec. 6, T.25-6)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, under Contract #31 dated April 7, 1853 (DCSO records, Volume 8 Page 3130)

Set post cor. to Tps. 24 & 25, & bet. Rgs. 6 & 7, from which
A Fir 36" dia., bears S.80½°W., 89 lks. dist.
A Fir 30" dia., bears N.7½°W., 122 lks. dist.
A Fir 28" dia., bears N.56¾°E., 97 lks. dist.
A Fir 44" dia., bears S.18°E., 70 lks. dist.

GLO survey by Whipple, 1893, found above corner and called out it to be 2.01 chs. South of Tsp. cor. for Tsp. 24 & 25 Rg. 7. (DCSO records, Volume 8 Page 3226)

BLM resurvey by Lynn Roseberry, under Group #645, Survey Aug./Sept. 1967 (DCSO records, Vol. 36 Page 14941)

Point for the cor. of tps. 24 and 25 S., R. 6 W., at record distance in latitude from the corner of secs. 30 and 31 only on the west boundary of T.24S R.6W.; and at record distance in departure from the cor. of secs. 5, 6, 31 and 32; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

		T 24 S
		R 6 W
T 25 S		S 31
R 7 W		S 6
S 1		T 25 S
		1967

from which
A Fir 14" dia. bears N.20¼°E. 83 lks mkd T24S R6W S31 BT
A Fir 10" dia. bears S.57°E., 26 lks mkd T25S R6W S6 BT.

DCSO-GIS Corner visitation - 5/12/2004 - Typed: 1/21/2011 - C.S. File 67/33-1

Monument - 2" IP/BC
Comment - OK