

PRIMARY CORNER DESCRIPTION C C Sec. Cor. for 19 & 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4001)

(Intersect the E. bdy. of T25S R9W, 6.29 chs. N. of the cor. of secs. 24 & 25.) At point of intersection, I set a Vine Maple post, 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 19 and 30 mkd. CC T25S R8W on E.; S19 on N.; and S30 on S. faces; with 2 grooves on S. and 4 grooves on N. faces; from which

A Fir 24" dia., bears N.40°30'E., 87 lks. dist. mkd. T25S R8W S19 BT.

A Fir 30" dia., bears S.57°20'E., 53 lks. dist. mkd. T25S R8W S30 BT.

BLM Resurvey by James E. Jelley and Jack W. Bowder, Cadastral Surveyors, under Group #767, Surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15049)

True point for the closing cor. of secs. 19 and 30. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 25 S	T 25 S	
	<u>S 19</u>	CC
R 9 W	S 30	
S 24	R 8 W	
	1972	

from which

A Hemlock 22" dia., bears N.27½°E., 150 lks. dist. mkd. T25S R8W S19 CC BT.

A Hemlock 25" dia., bears S.26°E., 19 lks. dist. mkd. T25S R8W S30 BT.

(Cor. of secs. 24 & 25 only, T25S R9W bears S.1°30'W., 6.43 chs. dist.)

From this point, the original closing cor., bears N.89°59'W., 0.49 chs. dist., monumented by person(s) unknown with an iron pipe, 1/2" dia., firmly set, projecting 6" above ground, from which the original bearing trees:

A Fir 40" dia., bears N.40°30'E., 87 lks. dist. with scribe marks S19 visible on partially healed blaze.

A Fir 33" dia., bears S.57°20'E., 53 lks. dist., with scribe marks BT visible on partially healed blaze.

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 - C.S. File 58/90

Found BLM monument with the following accessories:
(Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C C for Secs. 19 and 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

22" Hemlock bears N.27½°E., 150 lks.
25" Hemlock bears S.26°E., 19 lks.
From this point, the orig. closing cor. of sec. 19 & 30,
bears N.88°14.8'W., 26.64 ft., found 3/4" Iron pipe, from
which
40" D.Fir bears N.40½°E., 87 lks., orig. BT.
33" D.Fir bears S.57¼°E., 53 lks., orig. BT.