

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T25-9

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 10 Page(s) 3962)

 Set sandstone 28x14x10 ins., 21" in the ground for cor. of secs. 7, 12, 13 and 18 marked with 2 notches on the N. and 4 notches on the S. edges, from which
 A Fir 60" dia., bears N.70°E., 12 lks. dist. mkd. T25S R8W S7 BT.
 A Fir 64" dia., bears S.36¼°E., 32 lks. dist. mkd. T25S R8W S18 BT.
 A Fir 56" dia., bears S.5½°W., 35 lks. dist. mkd. T25S R9W S13 BT.
 A Fir 40" dia., bears N.14°W., 46 lks. dist. mkd. T25S R9W S12 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3969)

 The Sec. cor. which is a sandstone, firmly set, marked and witnessed as described by the Surveyor General, and which I now change to refer to secs.12 and 13 T25S R9W only.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept/Oct. 1968 - C.S. File 54/72-44

 Found - Sandstone called for with 4 notches on S. and 2 notches on N. sides.
 Orig. 60" now 68" Fir, alive, N.70°E., 7.9 ft., shows good scar.
 Orig. 64" now 70" Fir, alive, S.36¼°E., 21.1 ft., shows good scar.
 (The BTs above were mkd. before the closing cor. of secs. 7 & 18)
 Orig. 56" now 60" Fir, alive, S.5½°W., 23.1 ft., shows good scar. Rescribed "T25S R9W S13 CS BT"
 Orig. 40" now 48" Fir, alive, N.14°W., 30.4 ft., shows good scar. Rescribed "T25S R9W S12 CS BT"
 No smaller trees close.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 25 S	R
9	<u>S 12</u>	8
W	S 13	W

 1968

This corner lies on steep brushy South slope approx. 430 ft. South of ridge, course NE. and SW.