

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 and 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4008)

-----  
(Intersect the E. bdy. T25S R9W, 12.64 chs. N.0°35'E. of the cor. of secs. 12 & 13)

At point of intersection, I set a Cedar post 3 ft. long, 4" sq., 24" in the ground, for closing cor. for secs. 7 and 18, mkd. CC T25S R8W on E.; S7 on N.; and S18 on S. faces; with 4 grooves on S. and 2 grooves on N. faces; from which

A Hemlock 10" dia., bears N.43°30'E., 52 lks. dist., mkd. T25S R8W S7 BT.

A Hemlock 8" dia., bears S.22°30'E., 22 lks. dist. mkd. T25S R8W S18 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept/Oct. 1968 - C.S. File 54/72-42

-----  
Found - Orig. 10" now 20" Hemlock, alive, N.43½°E., 34.3 ft., shows good scar. Rescribed "T25S R8W S7 CC CS BT"

Orig. 8" now 9" Hemlock, alive, S.22½°E., 14.5 ft., scribe marks visible on unhealed blaze. We notch blaze overgrowth and count 50+ rings.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 25 S	R
9	S 7	8
W	S 18	W
	1968	

New BT - 11" Hemlock S.43½°E., 28.9 ft. mkd. T25S R8W S18 CC CS BT.

Corner lies on steep NE. slope 50 ft. N. of small spur, ridge sloping NW.