

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4011-12)

(Intersect the E. bdy. of T25S R9W, 13.85 chs. N.0°17'W. of the cor. of secs. 1 and 12)

At point of intersection, I set a Hemlock post, 3 ft. long, 4" sq., 24" in the ground for closing cor. for secs. 6 and 7, mkd. CC T25S R8W on E.; S6 on N.; and S7 on S. face; with 5 grooves on S. and 1 groove on N. face; from which

A Hemlock 30" dia., bears N.20°40'E., 67 lks. dist. mkd. T25S R8W S6 BT.

A Cedar 20" dia., bears S.83°E., 55 lks. dist. mkd. T25S R8W S7 BT.

Survey by Donald Peel -For: Weyerhaeuser Co. - May 1967 - C.S. File 55/30-4

Found - GLO survey record, post gone.
30" Hemlock N.20 3/4°E., 67 lks., now 36" Hemlock, scribe visible.
20" Cedar S.83°E., 55 lks., 24" Cedar, face not quite closed, scribe visible.

Set 4 ft. x 3/4" Pipe, 3 ft. in ground and square post.
Both BTs in good shape, so I just put Weyerhaeuser Co. plates with call distances and bearings on the original BTs.