

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4001)

Set a chinquapin post, 3 ft. long, 4" sq. 24" in the ground, for 1/4 sec. cor. marked 1/4 S19 on N & 30 on S face; from which
A fir, 30" dia., bears N.87°30'E., 72 lks., mkd: T25S R8W S19 BT.
A fir, 24" dia., bears S.3°20'E., 72 lks., mkd: 1/4 S30 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1968 - C.S. File 54/72-14

Found - Orig. 30" now 48" Fir, alive, N.87 1/2°E., 47.5 ft., shows good scar.
Orig. 24" now 36" Fir snag, S.3 1/3°E., 47.5 ft., open & find scribe.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W
OFFICE 1/4 S 19
1968 S 30

New BTs- 9" Hemlock, S.43 1/2°E., 21.3 ft. mkd: 1/4 S30 CS BT
11 D.Fir N.1°W., 9.3 ft., mkd: 1/4 S19 CS BT

This corner lies on moderate southerly slope approx. 150 ft. North of canyon bottom, course NW.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15048)

The 1/4 sec. cor. of secs. 19 & 30, perpetrated & recorded by Tracy, in 1968, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd. from which the orig. BTs

A fir, 48" dia., bears N.87°36'E., 72 lks., with healed blaze.

A fir, 44" dia., bears S.3°20'E., 72 lks. with fragmentary scribe marks visible on partially healed blaze.

and BTs by Tracy

A Fir, 10" dia., bears N.1°W., 14 lks., with scribe marks 1/4 S19 CS BT visible on open blaze.

A hemlock, 9" dia., bears S.43 1/2°E., 32 1/2 lks., with scribe marks 1/4 S30 CS BT visible on open blaze.

Henry R Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 - C.S. File 58/90 - M69-34

Found - Douglas Co. monument with the following accessories:
continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

48" D.Fir bears N.87°E., 72 lks. Orig. BT
44" D.Fir bears S.3¼°E., 72 lks. Orig. BT
10" D.Fir bears N.1°W., 14 lks. CS BT
9" Hemlock bears S.43½°E., 32½ lks. CS BT.