

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4005)

Set chinquapin post, 3 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor. marked ¼ S18 on N & 19 on S face; from which
A chinquapin, 13" dia., bears N.8°30'E., 49 lks., mkd: ¼ S18 BT.
A chinquapin, 10" dia., bears S.58°10'W., 18 lks., mkd: ¼ S19 BT.

Michael McDowell - For: Weyerhaeuser - April 15, 1977 - C.S. File 58/139-5

Found - 3/4" galvanized iron pipe from which:
A badly decayed chinquapin OBT stub (scribing visible) bears S.58°W., 12.0 feet.
A "W" nail RP in the base of a 14" hemlock bears N.47°E., 16.0 feet.
A "W" nail RP in the base of 16" hemlock bears S.01°W., 19.0 feet.

Tony Hostetter - For: Weyerhaeuser - March 7, 1986 - C.S. File 62/30-8

CORNER REPORT ONLY
Found - ¾" iron pipe.
18" hemlock stump Weyco tag & "W" nail bears N.47°E. 16.6 ft.
16" hemlock stump Weyco tag & "W" nail bears S.1°W., 19.6 ft.
Area logged in 1985. (See M64-59 & C.S. 58/139 for information from Michael S. McDowell, April 1977)