

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs. 7 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4008)

-----  
Set a rhododendron post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S7 on N & 18 on S faces; from which

A fir, 18" dia., bears S.37°E., 12 lks., mkd: ¼ S18 BT.

A hemlock, 24" dia., bears N.11°W., 46 lks., mkd: ¼ S7 BT.

-----  
Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Sept/Oct. 1968 - C.S. File 54/72-41

-----  
Found - Orig. 18" Fir, now dead & badly decayed, S.23°E. 7.9 ft. (Rec.S.37°E.) scribe visible on unhealed blaze.

Orig. 24", now 38" Hemlock, alive, N.11°W. 30.4 ft., shows fair scar. Rescribed "¼ S7 CS BT".

Set - Brass Cap at Cop. Mid: County Surveyors T25S R8W  
Office ¼ S 7  
1968 S 18

New BT - 18" Hemlock S.4°W., 34.2 ft. mkd: ¼ S188 CS BT.

This corner lies on steep east slope of main divide between bottom creek and Lake Creek about 66 ft. east of ridge top.