

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Secs 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3993-4)  
-----  
Set a dogwood post, 3 ft long 4" sq. 24" in the ground for sec. cor. marked ¼ S 31 on W and 32 on E face; from which  
    A fir, 16" dia., bears N.85°E., 26 lks., mkd: ¼ S32 BT.  
    A fir, 34" dia., bears N.0°30'W., 72 lks., mkd: ¼ S31 BT.

BLM administrative survey dated Oct. 1974 rec'd & filed 4/2018 - C.S. File 65/101-1  
-----  
Set - From Original BTs set 5 ft. iron fence post firmly in ground, from which  
    Fir snag, with visible scribing, bears N.2°E., 47.5 ft.  
    Fir, 26" dia., bears N.80°E., 17.2 ft.  
And tagged -  
    Cedar 10" dia., bears S.31°W., 5.9 ft.

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2018 - M174-25  
-----  
Found - Steel fence post which was set from 2 original BTs by BLM in 1974. (Unrecorded survey), from which:  
    34" Fir, OBT, BLM tag, bears; N.85°E., 17.2 ft to center.  
    Fir snag, OBT @ N.0°30'W., 47.5 ft is a windfall. (Standing in 1974, used to set corner)  
    15" Cedar, 1974 BT, BLM tag, S.31°W., 5.9 ft to center.

1