

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3994)

Set a yew post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 29, 30, 31, & 32 mkd: T25S S29 on NE, R8W S32 on SE, S31 on SW & S30 on NW faces; with 1 notch on S & 5 notches on E edges from which

- A cedar, 28" dia., bears N.67°50'E., 27 lks., mkd: T25S R8W S29 BT.
- A cedar, 24" dia., bears S.20°10'E., 47 lks., mkd: T25S R8W S32 BT.
- A cedar, 18" dia., bears S.20°15'W., 50 lks., mkd: T25S R8W S31 BT.
- A cedar, 30" dia., bears N.32°10'W., 18 lks., mkd: T25S R8W S30 BT.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15042-3)

The cor. of secs. 29, 30, 31, & 32, determined at rec. dist. from the remaining orig. BTs:

- A cedar, 20" dia., bears S.20°15'W., 50 lks., with fragmentary scribe marks visible on decayed blaze & a galvanized nail, with "W" embossed on the head, driven into base.
 - A cedar, 30" dia., bears N.28°W., 18 lks., with fragmentary scribe marks visible on decayed blaze & a galvanized nail, with "W" embossed on the head, driven into base. (Rec. N.32°10'W.)
- and BTs of which I have no record
- A cedar, 14" dia., bears N.87°E., 102 lks., with a galvanized nail, with "W" embossed on the head, driven into base.
 - A fir, 33" dia., bears S.28°E., 275 lks. with a galvanized nail with "W" embossed on the head, driven into base.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S	R8W
<u>S 30</u>	<u>S 29</u>
S 31	S 32
1972	

from which new BTs

- A hemlock, 8" dia., bears N.15½°E., 53 lks., mkd: ¼ S29 BT
- A hemlock, 10" dia., bears S.9½°E., 212 lks. mkd: ¼ S32 BT

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Henry R Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 - C.S.
File 58/90 - M69-34

Found - BLM monument with the following accessories:
36" cedar bears N.32°W., 11.9 ft. Orig. BT
20" cedar bears S.20°W., 50 lks. Orig. BT
14" cedar bears N.87°E., 102 lks.
33" D.Fir bears S.28°E., 275 lks.
8" Hemlock bears N.15½°E., 53 lks.
10" Hemlock bears S.9½°E., 212 lks.

FD 1972 BLM brass cap and accessories By T. Hostetter -
2/2018 - M174-25