

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3998)

Set fir post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. marked ¼ S30 on W & 29 on E faces; from which
A fir, 60" dia., bears S.65°E., 22 lks., mkd: ¼ S29 BT.
A fir, 65" dia., bears S.20°W., 22 lks., mkd: ¼ S30 BT.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15044-5)

The ¼ sec. cor. of secs. 29 & 30, determined at rec. distance from the orig. BTs:
A fir, 62" dia., bears S.81½°E., 22 lks., with healed blaze. (Rec. S.65°E.)
A fir, 50" dia., bears S.6½°W., 22 lks., with healed blaze. (Rec. S.20°W.)

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
¼
S 30|S 29
T25S R8W
1972

Henry R Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 - C.S. File 58/90 - M69-34

Found - BLM monument with the following accessories:
62" D.Fir bears S.81°E., 22 lks. Orig. BT (Rec. S.65°E)
50" D.Fir bears S.6½°W., 22 lks. Orig. BT (Rec. S.20°W)